#### **RHEEM PRESTIGE RESIDENTIAL TANKLESS**

# **CONDENSING TANKLESS SERIES**

Continuous hot water for 3 bathroom homes\*

## CRTGH-95DV indoor direct vent natural and LP models – 11.000 - 199.900 BTU max.

9.5 gal./min at 35° F rise max., 8.4 gal./min. at 45° F rise

Limited Warranty

### **12-Year on heat exchanger, 5-Year on parts, 1-Year on labour** See Residential Warranty Information Brochure for complete warranty information.

- 94% efficient with stainless steel condensing heat exchanger
- 2-Pipe Direct Vent System designed for ULC-S636 PVC or CPVC Pipe. See instructions for details.
- Up to 35 equivalent ft. of 3" Pipe or 5 equivalent ft. of 2" Pipe, ULC-S636 PVC or CPVC required. See instructions for details.
- Industry Best! .26 GPM Minimum Flow Rate, .40 GPM Minimum Activation Flow Rate
- Digital (UMC-117) remote control and 10 ft. of thermostat wire included
- EZ-Link™ cable available for high demand applications to connect two tankless units to operate as one
- Manifold up to 6 units with an optional MIC-6 manifold control board
- Manifold up to 20 units with the optional MIC-185 plus the MICS-185 manifold control assembly
- High-altitude capability up to 9,840 ft. elevation above sea level (no chip required)
- Exclusive! Guardian™ overheat film wrap (OFW)
- All Rheem tankless models are third-party efficiency listed by GAMA/AHRI
- Continuous hot water, energy saving and compact, space saving design
- Intelligent electronic controls designed to increase energy efficiency and safety
- Self Diagnostic System
- Digital display shows temperature setting and maintenance codes
- · Built-in electric blower
- Supplied with a 120 volt power cord
- Environmentally friendly Low NOx burner meets SCAQMD rule 1146 requirements
- Freeze protection to -35° F+

Product appearance may differ.

\* Based on simultaneous showers using 2.5 gallons per minute. Flow rates vary depending on temperature of cold water supply.

## The Condensing Series Tankless models can be converted for Commercial Installations

Tankless water heaters
Continuous hot water









S4-Energy Factor!





\*Digital remote control included.

See reverse for specifications.